


ANTI SLIP TAPE GLOW STRIPE – IS 53212 V

1.2 MM

PRODUCT DESCRIPTION

IS 53212 V Anti Slip Tape is a versatile solution that can be applied to almost any surface, instantly creating a slip-resistant area ready for immediate use. This mineral-coated, slip-resistant tape is designed to reduce trip hazards on smooth and flat surfaces, available in a wide range of colors and sizes to enhance personal safety. Combining high-quality abrasives with tough, durable adhesives, it provides outstanding slip resistance over long periods. Perfect for preventing slips and falls at home, it is important to avoid applying directly over tile grouting.

PRODUCT STRUCTURE



PRODUCT FEATURE

- **Mineral-Coated Surface:** Reduces trip hazards on smooth, flat surfaces.
- **Instant Anti-Slip Surface:** Provides immediate slip resistance upon application.
- **Enhances Safety:** Designed to improve personal safety by reducing the risk of slips and falls.
- **Wide Range of Colors and Sizes:** Available in various colors and sizes to fit different needs and preferences.
- **Durable and Long-Lasting:** Combines high-quality abrasives with durable adhesives for long-term performance.

PRODUCT APPLICATION

- **Mud-Prone Areas:** Ideal for areas where mud may be present.
- **Dry Areas:** Useful for dry areas like steps, ramps, ladders, and staircases.
- **Home Safety:** Enhances safety at home, particularly on slippery floors like marble and granite.
- **Accident Prevention:** Reduces the risk of accidents on slippery, uneven, or split-level floor surfaces.
- **High Durability:** Suitable for areas requiring extra strong traction, such as external ramps, sloping driveways, and loading docks.

PHYSICAL PROPERTIES

CHARACTERISTIC	UNIT	VALUE
COLOR	-	Black + Glow Stripe
BACKING	-	PVC Film
ADHESIVE TYPE	-	Solvent Based
THICKNESS	MM	1.2 ± 0.05
INITIAL TACK	STEEL BALL NO.	10
TENSILE STRENGTH	N/25MM	≥ 30
HOLDING POWER	H	≥ 24
PEEL ADHESION	N/25MM	≥ 10
ELONGATION	%	≥ 10
TEMPRATURE RESISTANT	°C	30 – 80
AFTERGLOW INTENSITY	MCD / SQM	10MIN ≥ 100 60MIN ≥ 12
AFTERGLOW TIME	MIN	≥ 1200

Information in the above sheet is the average value of the tests, it should not be taken as the exact values of every single product. Customers have the obligation to check whether the product is suitable for their own applications.

STORAGE AND USAGE

Tape should be stored in dry, cool, shelter area and avoid direct sunlight, storage temperature under 40°C under correct storage conditions maintains its characteristics for two years.

NOTICE

- Please try a sample and make sure the tape is suitable for the application before use it.
- Customers who buy the jumbo rolls should stop the re-winding and slitting once find that there has quality problem with the jumbo. Contact us right away. If customers re-wind/cut the problematic jumbo into log/finished rolls, Instabiz Solutions India Pvt. Ltd. will not response to make any indemnity.
- Ideal tape application temperature is 8 to 38 Celsius. It is not suggested to use the tape below zero Celsius, because the adhesive will become too firm to adhere readily. However, once customers insist on using the tape under such a low temperature, please contact us, Instabiz Solutions India Pvt. Ltd. will adjust the adhesive, but Instabiz Solutions India Pvt. Ltd. doesn't guarantee anything.
- Firm application pressure helps develop better adhesive contact and improves bond strength, the bonding surfaces must be clean, dry and well unified. Seal completely when not use the tape, avoid expose the tape in the sunlight.
- Expiry date: Original packaging, 23 C & 60% humidity, 12 months after production date. If product is not kept under such temperature and humidity, jumbo/log rolls should be finished within four months, finished rolls should be finished within one month.
- All Instabiz Solutions India Pvt. Ltd. products are strict inspected before sent to customers, but the applications might be different between different customers, there may exist factors which are beyond Instabiz Solutions India Pvt. Ltd. knowledge and control, so customers should check the quality of every order before use the tape. If customers use the product without inspection, they must be responsible for the potential quality problems and economic loss. If the product is proved to be defective, the exclusive remedy, at Instabiz Solutions India Pvt. Ltd. option, shall be to refund the purchase price of or replace the problematic product.

info@instabizsolutions.com

www.instabizsolutions.com